## (19) World Intellectual Property Organization International Bureau





(43) International Publication Date 25 August 2005 (25.08.2005)

**PCT** 

(10) International Publication Number WO 2005/079073 A1

- (51) International Patent Classification?: H04N 7/26, 7/30
- (21) International Application Number:

PCT/EP2004/013592

(22) International Filing Date:

30 November 2004 (30.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 04003194.0

12 February 2004 (12.02.2004) EF

(71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).


(72) Inventors; and

(75) Inventors/Applicants (for US only): WEDI, Thomas [DE/DE]; Aussiegerstrasse 8, 64823 Gross-Umstadt (DE). WITTMANN, Steffen [DE/DE]; Hermesstrasse 18, 63263 Neu-Isenburg (DE).

- (74) Agent: KAYSER, Andreas; Grünecker, Kinkeldey, Stockmair & Schwanhäusser, Maximilianstrasse 58, 80538 München (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: ENCODING AND DECODING OF VIDEO IMAGES BASED ON A QUANTIZATION WITH AN ADAPTIVE DEAD-



(57) Abstract: The present invention enables to control the encoding of film grain information without adversely affecting the overall coding efficiency of the encoding process of video data. For this purpose, a control of the size of the quantization interval for the lowest transform coefficient values is separated from a control of fitting the quantization interval and the quantized value to a probability distribution of the transform coefficient values. This is accomplished by providing a dead-zone parameter to be taken into account by the quantization process and the de-quantization process.

BEST AVAILABLE COP

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



